

Flushing kit



The flushing kit allows flushing the refrigerant circuit for air conditioners with refrigerant R1234yf and R134a.

**REFRIGERANT
R134a & R1234yf**

Rinsing kit consisting of

- Flushing/flushing kit
- Adapter for various refrigerants
- Adapter for various threaded connections
- Micro-filter

Highlights

Easy handling - fast application

- Fully automatic flushing in the circuit with liquid refrigerant against the flow direction of the A/C system in the commercial vehicle
- Adapter or adapter kit required (available from us on request)
- Very high flow rate during flushing and thus high cleaning performance of the A/C system
- 1 filter that can be easily replaced after 5 cycles

Flexible for different needs

- Can be used for the refrigerant R134a and the new refrigerant R1234yf
- Can also be used on A/C units with different threaded connections
- An optional bracket (W067130135) is available for mounting the flushing kit directly to the A/C service unit.



Can be mounted directly on the air-conditioning service unit via bracket

Technical data

Type	R134-R1234FK 5L
Refrigerant tank	~ 5000ml
Refrigerant	R134a and R1234yf
Max. operating pressure	20 bar
Number of filters	1
Max. ambient temperature	50 °C

Have you also thought about materials and accessories such as refrigerants, oils, UV leak detection additive or UV LED flashlight? Available in the Würth Online Shop at www.eshop.wuerth.de